

The effect of high-Z material injection on runaway electron dynamics

G. Papp¹, ASDEX Upgrade Team¹, TCV Team^{2*}, and the EUROfusion MST1 Team^{**}.

¹Max-Planck-Institute for Plasma Physics, Garching, Germany; ²Swiss Plasma Centre, EPFL, Lausanne, Switzerland; *See the author list of “S. Coda et al NF [57 102011 \(2017\)](#)”

**See the author list of “H. Meyer et al NF [57 102014 \(2017\)](#)”.

Developing a disruption & runaway electron (RE) mitigation strategy that robustly scales to ITER and beyond is a major challenge. The dynamics is governed by a complex interplay of effects such as the atomic physics and penetration of the high-Z material injected for mitigation, quench dynamics (MHD), kinetic physics, and quantum mechanics. The EUROfusion consortium is executing a coordinated research program to better understand the generation^{1,2}, control³ and mitigation⁴ of disruption-born REs following massive material injection.

RE studies on ASDEX Upgrade and TCV are carried out using massive gas injection (MGI) of neon, argon and krypton. The injection of high-Z materials mixed with deuterium is a promising mitigation strategy for ITER. A 1:4 argon-deuterium mixture has prevented RE beam formation in the commonly used RE scenario on ASDEX Upgrade. TCV demonstrated RE beam control up to a pre-disruption elongation of $\kappa \simeq 1.5$. Our results indicate that increasing elongation has no significant impact on RE physics and the main challenge is position control.

The scaling of the initial runaway current on plasma- and injection parameters, as well as the subsequent dissipation is analysed using 1D disruption-runaway simulations^{5,6} along with state-of-the-art full-f kinetic models⁷. The high-Z dissipation model⁷ was validated using experimental data from multiple European tokamaks. Full-f kinetic simulations were carried out for the first time for the complete duration of the thermal & current quench. These simulations show that an abrupt delivery of high-Z material (e.g. executed by SPI) is expected to significantly decrease the RE generation rate compared to slower injections methods (such as MGI).

References

- [1] G. PAUTASSO ET AL. Plasma Physics and Controlled Fusion, [59 \(1\):014046 \(2017\)](#).
- [2] J. MLYNAR ET AL. Plasma Physics and Controlled Fusion, [61 \(1\):014010 \(2019\)](#).
- [3] D. CARNEVALE ET AL. Plasma Physics and Controlled Fusion, [61 \(1\):014036 \(2018\)](#).
- [4] G. PAPP ET AL. IAEA-FEC, [IAEA-CN-234-0502:EX/9 \(2016\)](#).
- [5] G. PAPP ET AL. Nuclear Fusion, [53 \(12\):123017 \(2013\)](#).
- [6] E. FABLE ET AL. Nuclear Fusion, [56 \(2\):026012 \(2016\)](#).
- [7] L. HESSLOW ET AL. Plasma Physics and Controlled Fusion, [60 \(7\):074010 \(2018\)](#).